

■ SINGLE TURNS/SURFACE MOUNT

82	91	93
1/4" (6.35mm)	3/8" (9.53mm)	1/2" (12.70mm)
220°	174°	270°
10~2MΩ	10~2MΩ	10~2M
±10% (<100Ω=±20%)	±20%	±20% (<100Ω=±20%)
±100 (<100Ω=±250)	±100 (<100Ω=±250)	±100 (<100Ω=±250)
1% (<100Ω=1Ω)	1% (<100Ω=1Ω)	1% (<100Ω=1Ω)
85℃ Fluorinert	Dust Cover	85℃ Fluorinert
82M② 82P①, PF 82W③	91A③, 91B② 91C④, 91E⑦	93P②
82PA②	91T, X② 91V⑥ 91W③	
Standard	Standard	Standard
M, P, PA, W	N/A	N/A
WF(Not e C)	N/A	N/A
WF(Not e C)	N/A	N/A

Model	22	23
Size(Not e A)	0.118" (3mm)	0.157" (4mm)
Electrical Travel	220°	220°/210°
Resistance Range	100~1MΩ	100~2MΩ
Tolerance	±20%	±20%
TCR(ppm/℃)	±100 (<200Ω=±250)	±100 (<200Ω=±250)
Contact Resistance Variance Max.	3%	2% (<200Ω=±250)
Seal	85℃ Fluorinert	85℃ Fluorinert
Adjustment style		
Top	22A③ 22B①	23A③ 23B
Side, Edge Mount		23S③
Bottom		
Packing Options		
Bulk	Standard	N/A
Tubes	N/A	N/A
Tape&Reel	N/A	Standard
Ammo Pack	N/A	N/A

■ PC BOARD PATTERNS/SURFACE MOUNT/inch (mm)

