

PS2 SMD SMART PROTECTOR

PS2 models use a Cu alloy fusing element with FeCuSn end plates housed in a ceramic

body and sealed with inorganic molding. These models have UL approval. File number:

E238986 for 1-15A. They are also RoHS compliant. Applications include: LCD inverters.



■ GENERAL SPECIFICATIONS

Catalog Number	Ampere Rating(A)	Voltage Rating(V)	Nominal Resistance Cold ohms(Ω)
1A00	1.00	125	0.165
2A00	2.00		0.063
2A50	2.50		0.052
3A15	3.15		0.040
4A00	4.00		0.032
5A00	5.00		0.020
6A30	6.30		0.018
7A00	7.00		0.015
8A00	8.00		0.011
10A0	10.00		0.008
12A0	12.00		0.006
15A0	15.00		0.004

■ CHARACTERISTICS

Open	Opening time	% of Ampere Rating
	4 hours minimum	100%
	10 seconds maximum	200%
Dump heat, steady state	±(5%+0.1Ω) 25±1℃, 90~95%RH, 1.5hours on/ 0.5hours off cycle, 1000hours	
Endurance	±(10%+0.1Ω) 1 cycle: 15 minutes on, 4 minutes off, 100 cycle	
Soldering method	Wavesolder: 260℃ 10 secs maximum	
Insulation	The insulation resistance between fuse terminals shall be 0.1 MΩ minimum measured by 500V dc insulation tester. 100 cycle of rated current (DC.) carry for 1 hour, then switch off for 15 minutes. Followed by 1 hour at 1.5 hours	

■ ELECTRICAL CHARACTERISTICS

% of Ampere Rating	Opening Time
100%	4 hours, minimum
200%	10 seconds minimum

■ DIMENSIONS [mm]

Model	Dimension(mm)						
	L±0.5	W±0.3	T±0.3	A±0.3	B±0.5	D±1.8	
PS2	6.3	3.3	2.8	1.4	1.2	1.8	

■ ORDERING PROCEDURE EXAMPLE

PS2	125	S	E	1A00
Model #	Voltage Rating	Style	Electrical Characteristics	Ampere Rating
	125:125V	S: SMD Type	F: Fast acting	1A00: 1A